

Brass Compression Fittings / Complementary Fittings

0126 Plug for Compression Fitting

Brass



ØD		L	Kg
4	0126 04 00	10	0.002
6	0126 06 00	10	0.003
8	0126 08 00	11.5	0.006
10	0126 10 00	13	0.010
12	0126 12 00	13	0.014
14	0126 14 00	13.5	0.020
18	0126 18 00	16	0.038
22	0126 22 00	18	0.003

The plug is used to blank off an outlet in a compression fitting, replacing the olive.
When an open outlet is required, simply dismantle and replace the plug with the tube olive, reusing the nut.
The plug is also reusable.

0125 Tube End Plug for Compression Fitting

Brass




ØD	C	F	L	L1	Kg	
4	M8x1	0125 04 00	10	12	8	0.005
6	M10x1	0125 06 00	11	13.5	9.5	0.008
8	M12x1	0125 08 00	14	14	9	0.013
10	M16x1.5	0125 10 00	17	18	11	0.025

This plug enables unused tubes to be blanked off.
The male thread on the plug has the same pitch as the female thread on the sleeve nut of a standard Parker Legris fitting.
Therefore the plug screwed into the sleeve nut blanks off the tube.
To reopen the passage, simply unscrew the plug and fit the required coupler.
No further treatment of the tube is required.

0220 Hex Head Plug, Male BSPP and Metric Thread

Brass, technical polymer




C	F	G	H1	Kg	
M5x0.8	0220 19 00	8	8	5	0.002
G1/8	0220 10 00	14	14	7.5	0.011
G1/4	0220 13 00	17	17	7.5	0.020
G3/8	0220 17 00	17	22	8.5	0.024
G1/2	0220 21 00	22	27	10	0.041

Thread with pre-assembled sealing washer
M5: with screwdriver slot for tightening
Maximum allowable working pressure = 20 bar
Conforms to BNA 229 (with the exception of M5 model), BSPP thread, ISO ISO 228-1, Parallel metric thread, ISO NFE 03-054.

0220..39 Hex Head Plug with Bi-Material Seal, Male BSPP Thread

Brass, zinc plated steel with NBR seal




C	F	G	H	Kg	
G1/8	0220 10 00 39	14	14	6.5	0.012
G1/4	0220 13 00 39	17	17	6.5	0.020
G3/8	0220 17 00 39	17	22	8	0.025
G1/2	0220 21 00 39	22	26	9	0.042
G3/4	0220 27 00 39	22	32	10	0.059
G1	0220 34 00 39	27	39.5	10.5	0.088

Plug with bi-material seal
Bi-material washers part number 0139 can be found in sub-chapter "Adaptors and Manifolds".
Part Number with suffix 39, maximum allowable working pressure: 250 bar

0120 Stud Standpipe, Male BSPT Thread

Brass



ØD	C	F	L	L1	Kg	
4	R1/8	0120 04 10	11	25.5	14	0.007
5	R1/8	0120 05 10	11	26	14.5	0.007
6	R1/8	0120 06 10	11	26.5	15	0.008
	R1/4	0120 06 13	14	31	15	0.015
8	R1/8	0120 08 10	11	28.5	17	0.009
	R1/4	0120 08 13	14	33	17	0.016
	R3/8	0120 08 17	17	33.5	17	0.020
10	R1/4	0120 10 13	14	36	20	0.017
	R3/8	0120 10 17	17	36.5	20	0.022
	R1/2	0120 10 21	22	41	20	0.039
12	R1/4	0120 12 13	14	36	20	0.017
	R3/8	0120 12 17	17	36.5	20	0.022
	R1/2	0120 12 21	22	41	20	0.040
14	R3/8	0120 14 17	17	38	21.5	0.023
	R1/2	0120 14 21	22	42.5	21.5	0.042
15	R3/8	0120 15 17	17	38	21.5	0.023
	R1/2	0120 15 21	22	42.5	21.5	0.040
16	R3/8	0120 16 17	17	39.5	23	0.024
	R1/2	0120 16 21	22	44	23	0.042
18	R1/2	0120 18 21	22	44.5	23.5	0.042
	R3/4	0120 18 27	27	47.5	23.5	0.070
20	R3/4	0120 20 27	27	49	25	0.070
22	R3/4	0120 22 27	27	48.5	25.5	0.067
	R1	0120 22 34	36	52.5	25.5	0.117
28	R1	0120 28 34	36	57	30	0.140

Assembly: Barb Connectors

Our barb connectors 0122 and 0165 are designed to be used with different types of hose. They are secured using the nut and olive provided with the fitting.

