







Ø 16,5 25 40	 	COT 90° <table><tr><th>Transair®</th><th>Ø D</th><th>Ø G</th><th>L</th><th>Z</th><th>Kg</th></tr><tr><td>6602 17 00</td><td>16,5</td><td>34</td><td>58</td><td>31</td><td>0,065</td></tr><tr><td>6602 25 00</td><td>25</td><td>44,5</td><td>69,5</td><td>40</td><td>0,120</td></tr><tr><td>6602 40 00</td><td>40</td><td>67</td><td>103</td><td>62</td><td>0,410</td></tr></table>	Transair®	Ø D	Ø G	L	Z	Kg	6602 17 00	16,5	34	58	31	0,065	6602 25 00	25	44,5	69,5	40	0,120	6602 40 00	40	67	103	62	0,410
Transair®	Ø D	Ø G	L	Z	Kg																					
6602 17 00	16,5	34	58	31	0,065																					
6602 25 00	25	44,5	69,5	40	0,120																					
6602 40 00	40	67	103	62	0,410																					
Ø 50 63	 	<table><tr><th>Transair®</th><th>Ø D</th><th>Ø G</th><th>L</th><th>Z</th><th>Kg</th></tr><tr><td>6602 50 00</td><td>50</td><td>80</td><td>116</td><td>56</td><td>0,804</td></tr><tr><td>6602 63 00</td><td>63</td><td>91</td><td>124</td><td>61</td><td>0,970</td></tr></table>	Transair®	Ø D	Ø G	L	Z	Kg	6602 50 00	50	80	116	56	0,804	6602 63 00	63	91	124	61	0,970						
Transair®	Ø D	Ø G	L	Z	Kg																					
6602 50 00	50	80	116	56	0,804																					
6602 63 00	63	91	124	61	0,970																					
Ø 76 100 168	 	<table><tr><th>Transair®</th><th>Ø D</th><th>H</th><th>Z</th><th>Kg</th></tr><tr><td>RX02 L1 00</td><td>76</td><td>227</td><td>189</td><td>1,033</td></tr><tr><td>RX02 L3 00</td><td>100</td><td>278</td><td>227</td><td>1,417</td></tr><tr><td>RA02 L8 00</td><td>168</td><td>269</td><td>185</td><td>3,074</td></tr></table> Utilizați 2 racorduri RR01 pentru a conecta coturile de 90° RX12 și RA02 la conducta din aluminiu Transair® cu Ø 76, Ø 100 sau Ø 168.	Transair®	Ø D	H	Z	Kg	RX02 L1 00	76	227	189	1,033	RX02 L3 00	100	278	227	1,417	RA02 L8 00	168	269	185	3,074				
Transair®	Ø D	H	Z	Kg																						
RX02 L1 00	76	227	189	1,033																						
RX02 L3 00	100	278	227	1,417																						
RA02 L8 00	168	269	185	3,074																						

Ø 25 40	 	COT 45° <table><tr><th>Transair®</th><th>Ø D</th><th>Ø G</th><th>L</th><th>Z</th><th>Kg</th></tr><tr><td>6612 25 00</td><td>25</td><td>44,5</td><td>61,5</td><td>32,5</td><td>0,115</td></tr><tr><td>6612 40 00</td><td>40</td><td>67</td><td>90</td><td>45</td><td>0,370</td></tr></table>	Transair®	Ø D	Ø G	L	Z	Kg	6612 25 00	25	44,5	61,5	32,5	0,115	6612 40 00	40	67	90	45	0,370		
Transair®	Ø D	Ø G	L	Z	Kg																	
6612 25 00	25	44,5	61,5	32,5	0,115																	
6612 40 00	40	67	90	45	0,370																	
Ø 50 63	 	<table><tr><th>Transair®</th><th>Ø D</th><th>Ø G</th><th>L</th><th>Z</th><th>Kg</th></tr><tr><td>6612 50 00</td><td>50</td><td>80</td><td>98</td><td>38</td><td>0,771</td></tr><tr><td>6612 63 00</td><td>63</td><td>91</td><td>100</td><td>37</td><td>0,906</td></tr></table>	Transair®	Ø D	Ø G	L	Z	Kg	6612 50 00	50	80	98	38	0,771	6612 63 00	63	91	100	37	0,906		
Transair®	Ø D	Ø G	L	Z	Kg																	
6612 50 00	50	80	98	38	0,771																	
6612 63 00	63	91	100	37	0,906																	
Ø 76 100 168	 	<table><tr><th>Transair®</th><th>Ø D</th><th>L1</th><th>Z</th><th>Kg</th></tr><tr><td>RX12 L1 00</td><td>76</td><td>235,5</td><td>122</td><td>0,704</td></tr><tr><td>RX12 L3 00</td><td>100</td><td>271,4</td><td>138</td><td>1,309</td></tr><tr><td>RA12 L8 00</td><td>168</td><td>310,5</td><td>147,5</td><td>2,366</td></tr></table> Utilizați 2 racorduri RR01 pentru a conecta coturile de 45° RX12 și RA12 la conducta din aluminiu Transair® cu Ø 76, Ø 100 sau Ø 168.	Transair®	Ø D	L1	Z	Kg	RX12 L1 00	76	235,5	122	0,704	RX12 L3 00	100	271,4	138	1,309	RA12 L8 00	168	310,5	147,5	2,366
Transair®	Ø D	L1	Z	Kg																		
RX12 L1 00	76	235,5	122	0,704																		
RX12 L3 00	100	271,4	138	1,309																		
RA12 L8 00	168	310,5	147,5	2,366																		